

HADK-T120S

AIR HAMMER (SD12)



Key features

- Robust SD12 Shank Design
- Superior Technology
- Standard bit diameters 11 7/8"-17 1/2" (302-445mm)
- Delivers more energy per blow
- Hardened piston for extended life
- Repair & Rebuild kits available for easy and cost effective maintenance

Parts List (SD12)

NO	Part Name	Qty	Part Number
1	Top Sub	1	HPDK-T12002
2	Top Sub O-Ring	1	See Sealkit
3	Wear Washer	2	HPDK-T12004
4	Spring	1	HPDK-T12006
5	Check Valve	1	HPDK-T12007
6	C.V. Spring	1	HPDK-T12009
7	Choke Set	1	HPDK-T12008
8	Air Distributor	1	HPDK-T12010
9	Air Dis. O-Ring	1	See Sealkit
10	Cylinder	1	HPDK-T12012
11	Cyl Ret Ring	1	HPDK-T12013
12	Piston	1	HPDK-T12014
13	Wear Sleeve	1	HPDK-T12001
14	Bit Ret. Ring O-Ring	1	See Sealkit
15	Bit Ret. Ring	1	HPDK-T12018
16	Piston Ret. Ring	1	HPDK-T12017
17	Bearing	1	HPDK-T12020
18	Drive Sub	1	HPDK-T12022
	Sealkit (Items 2, 9, 14)	1	HPDK-T120SSEALKIT
	Complete Hammer		HADK-T120S

Dimensions & Weights

Top Sub Connection	6 5/8" API REG PIN
Eff. Length (in / mm)	70.31 / 1786
OD (in / mm)	10.8 / 274
Hammer Weight (lbs / Kg)	1433 / 650
Piston Weight (lbs / Kg)	264 / 120


Drilling Parameters

Working Pressure (PSI / Bar)	150-250 / 10.3-17.2
Application Bit (in / mm)	11 7/8-17 1/2 / 302-445
Rotation Speed (RPM)	15-25
Assembly Make-Up Torque (lb-Ft / N-m)	12000 / 16272
Rotation Torque (lb-Ft / N-m)	6500 / 8814
Frequency (blows / min)	1200

Air Consumption

PSI	BAR	CFM	M³/Min
150	10.3	880	25
200	13.9	1250	35
250	17.3	1700	48

Exploded view



Note: Drilling Parameters given are guideline only