Drill King International

HABC-20

DTH HAMMER (DK20)



Key features

- BR2 design
- Valved design for low air pressures
- Standard bit diameters, 2.75”-3.5” (70-90mm)
- Repair & Rebuild kits available for easy and cost effective maintenance

TECHNICAL BROCHURE

Part List (DK20)

NO	Part Name	QTY	Part Number
1	Top Sub	1	HPDK02002-PIN
2	Top Sub O-Ring	1	HPDK02003
3	Check Valve	1	HPDK02007
4	C.V. Spring	1	HPDK02009
5	Guide	1	HPDK02004
6	Centralizer	1	HPDK02006
7	Disk Valve	1	HPDK02005
8	Choke Set	1	HPDK02008
9	Air Distributor	1	HPDK02010
10	Piston	1	HPDK02014
11	Cylinder	1	HPDK02012
12	Bit Bearing	1	HPDK02020
13	Wear Sleeve	1	HPDK02001
14	Spacer	1	HPDK02023
15	Bit Ret. Ring	1	HPDK02018
16	Chuck Seal	1	HPDK02024
17	Chuck	1	HPDK02022
	Repair kit (Items 2, 3, 4, 6, 7, 8,15,16,17)		HPDK02-BR2REPKIT
	Complete Hammer		**HABC20**

Dimensions & Weights

Top Sub connection	W + H Taper Pin
Eff. Length (in / mm)	29.4 / 747
OD (in / mm)	2.44 / 62
Hammer Weight (lbs / Kg)	28.6 / 13
Piston Weight (lbs / Kg)	4 / 1.82


Drilling Parameters

Working Pressure (PSI / Bar)	100-250 / 6.9-17.2
Application Bit (in / mm)	2.75-3.5 / 70-90
Rotation Speed (RPM)	23-28
Assembly Make-Up Torque (lb·Ft / N·m)	1500 / 2034
Rotation Torque (lb·Ft / N·m)	350 / 475
Frequency (blows / min)	979 -1548

Air Consumption

PSI	BAR	CFM	M3 /Min
100	7	27	0.75
150	10.3	49	1.4
200	13.8	76	2.13
250	17.2	105	2.98

Exploded view



Note: Drilling Parameters given are guideline only

Drill King International

Phone: Global - **1.817.539.2500** or US/Canada - **1.866.900.2487**
Email: **sales@drillking.com** Web: **www.drillking.com**
Drill King International L.P. | 820 South 6th Avenue, Mansfield, TX 76063, USA