Drill King International

HADK-A40I

DTH HAMMER (IR340)



Key features

- Repair & Rebuild kits available for easy and cost effective maintenance
- High frequency design for fastest penetration rates
- Available for other common bits shanks QL and SD
- Customizable options for open hole or cased hole projects

TECHNICAL BROCHURE

Parts List (IR340)

NO	Part Name	Qty	Part Number
1	Top Sub	1	HPDK-A4002
2	Top Sub O-Ring	1	HPDK-A4003
3	Choke Set	1	HPDK-A4008
4	Check Valve	1	HPDK-A4007
5	C.V. Spring	1	HPDK-A4009
6	Spacer Ring	1	HPDK-A4005
7	Make Up Ring	1	HPDK-A4006
8	Air Distributor	1	HPDK-A4010
9	Air Dis. O-Ring	1	HPDK-A4011
10	Cylinder	1	HPDK-A4012
11	Piston	1	HPDK-A4014
12	Wear Sleeve	1	HPDK-A4001
13	Piston Ret. Ring	1	HPDK-A4017
14	Bit Bearing	1	HPDK-A4020
15	Bit Ret. Ring	1	HPDK-A4018
16	Bit Ret. Ring O-Ring	1	HPDK-A4019
17	Drive Sub	1	HPDK-A4022
	Sealkit (Items 2, 9, 16)		HPDK-A40SEALKIT
	Complete Hammer		**HADK-A40I**

Dimensions & Weights

Top Sub Connection	2-3/8 API REG PIN
Eff. Length (in / mm)	36.41 / 924.8
OD (in / mm)	3.86 / 98
Hammer Weight (lbs / Kg)	84 / 38.1
Piston Weight (lbs / Kg)	16.3 / 7.4


Drilling Parameters

Working Pressure (PSI / Bar)	150-350 / 10.3-24
Application Bit (in / mm)	4-5 / 101-127
Rotation Speed (RPM)	20-45
Assembly Make-Up Torque (lb·Ft / N·m)	2000 / 2712
Rotation Torque (lb·Ft / N·m)	600 / 815
Frequency (blows / min)	1350

Air Consumption

PSI	BAR	CFM	M^3/Min
150	10.3	230	6.5
250	17.2	425	12
350	24.1	640	18.1

Exploded view



Note: Drilling Parameters given are guideline only

Drill King International

Phone: Global - **1.817.539.2500** or US/Canada - **1.866.900.2487**
Email: **sales@drillking.com** Web: **www.drillking.com**
Drill King International L.P. | 820 South 6th Avenue, Mansfield, TX 76063, USA