

HADK-A50S

AIR HAMMER (SD5)



Key features

- Innovative & simple design for easy eco kit maintenance
- High frequency design for fastest penetration rates
- Available for common bits shanks IR/QL/SD
- Customizable options for open hole or cased hole projects
- Premium alloys & treatment used for longer lasting tools

Parts List (SD5)

NO	Part Name	Qty	Part Number
1	Top Sub	1	HPDK-A5002
2	Top Sub O-Ring	1	HPDK-A5003
3	Choke Set	1	HPDK-A5008
4	Check Valve	1	HPDK-A5007
5	C.V. Spring	1	HPDK-A5009
6	Spring Washer	1	HPDK-A5005
7	Make Up Ring	1	HPDK-A5006
8	Air Distributor	1	HPDK-A5010
9	Air Dis. O-Ring	1	HPDK-A5011
10	Cylinder	1	HPDK-A5012
11	Piston	1	HPDK-A5014-S
12	Wear Sleeve	1	HPDK-A5001-S
13	Snap Ring	1	HPDK-A5021
14	Bit Bearing	1	HPDK-A5020-S
15	Bit Ret. Ring	1	HPDK-A5018-S
16	Bit Ret. Ring O-Ring	1	HPDK-A5019
17	Drive Sub	1	HPDK-A5022-S
Complete Hammer			HPDK-A50S
Sealkit (Items 2, 9, 16)			HPDK-A50SEALKIT

Dimensions & Weights

Top Sub	3 1/2" API REG PIN
OAL (in / mm)	46.7 / 1186
OD Range (in / mm)	4.76 / 121
Weight w/o bit (lbs / Kg)	137 / 62.1
Piston Weight (lbs / Kg)	25 / 11.3

Drilling Parameters

Working Pressure (PSI / Bar)	150-350 / 10.3-24.1
Application Bit (in / mm)	5-6 / 127-152
Feed Force (FT-lbs / M-Kg)	1000-3000 / 138-415
Rotation Speed	15-40 RPM
Rotation Torque (FT-lbs / M-Kg)	2380 / 329
Frequency (blows / min)	1540

Air Consumption

PSI	BAR	CFM	CuMtr/Min
150	10.3	310	8.8
250	17.2	555	15.7
350	24.1	720	20.4

Exploded view

